

CV-N22DC



Features

- Shortest Path By Vector Drive Technology
- Endless 360 Degrees Pan Rotation
- Independent Preset Characteristic Setup
- 128 Preset Positions
- 4 Pattern, 8 Swing, and 8 Group Functions
- Auto Flip, Auto Parking, Power-up Action
- Built-in Sensor In Function (4 In / 2 Out)
- Vandal Resistant, Day & Night (DSS)
- RS-485 Communication, Pelco-D

Specification

Optional Accessory

CVB100: Ceiling Mount Bracket



Image Sensor	1/4" Sony Super HAD CCD
Effective Pixels Number	768(H) x 494(V) 380K Pixels
Resolution	480 TV Lines
Sensitivity	Day (1.0 Lux), Night (0.001 Lux)
Scanning Area	4.9(H) x 3.7(V)mm
Scanning System	2:1 Interlaced NTSC Standard
Lens	3.9~85.8mm Power Zoom Lens
Zoom Magnification	22x Optical Zoom, 10x Digital Zoom
Sync System	Internal
Electronic Iris	1/60 ~ 100,000 sec
AGC, BLC, Flickerless	On / Off Selectable
Focus	Auto / Manual / Semi-Auto
AE Mode	Auto / Iris / Shutter / Manual
S/N Ratio	More Than 48dB
Power Source	AC24V (2 Amp Recommended)
Dimensions	Dome: 7" Diameter Housing: 8.5" (H) x 6.5" (W)
Ambient	Temp. -22°F ~ 122°F
Weight	Approx. 6 lbs